



สายท่อลม-แก๊ส คู่

Twin Line Welding Hose

KOVET and Alibaba TWIN LINE WELDING HOSE

Conform to BS: EN 559:1994

ISO: 5651



KOVET and Alibaba industrial hose offer a complete range of twin welding gas hose. From the small bore hose for lapidary work to various standard bore hose for many different industries including construction, manufacturing, mining, metal working, automotive industry, oil industry, ship building and more. They are especially designed 2 braid reinforcement for heavy-duty work.



Alibaba

LINING: Black synthetic rubber blend

REINFORCEMENT: High strength textile filament yarn

COVER: Excellent ozone and weather resistant synthetic rubber

COLOR: Red & Green, Red & Black, or Red & Blue

WORKING TEMPERATURE: -25°C TO + 80°C

SAFETY FACTOR: 3:1



ลักษณะเด่น

มีความทนทานต่อสภาพการทำงานปกติ และสภาพอากาศในการทำงานเชื่อม โดยมียางสังเคราะห์ SBR เป็นส่วนประกอบสำคัญ และมีใย Filament Synthetic เป็นแรงดันเสริมได้สูง

- ใช้ได้ในงานเชื่อม งานตัด ทุกชนิด
- เป็นสายผ่านลม และสายผ่านแก๊ส เช่น Acetylene, LPG
- สามารถใช้ในงาน Air Tools และน้ำ ภายใต้อแรงดัน

KOVET TWIN LINE WELDING HOSE (Black-Red)

ขนาด Nominal ID	เส้นผ่าศูนย์กลาง		ความยาว Length	แรงดันทานเสริม Reinforcement Braid	แรงดันขณะทำงาน Working Pressure	
	วงใน Inside Diameter	วงนอก Outside Diameter			psi	bar
3/16"	5.0 + 5.0 mm	12.0 + 12.0 mm	100 m/roll	2 B	300	20
1/4"	6.0 + 6.0 mm	13.0 + 13.0 mm	100 m/roll	2 B	300	20
1/4" x 3/8"	6.0 + 9.0 mm	13.0 + 16.0 mm	100 m/roll	2 B	300	20
5/16"	8.0 + 8.0 mm	15.0 + 15.0 mm	100 m/roll	2 B	300	20

Alibaba TWIN LINE WELDING HOSE (Green-Red)

ขนาด Nominal ID	เส้นผ่าศูนย์กลาง		ความยาว Length	แรงดันทานเสริม Reinforcement Braid	แรงดันขณะทำงาน Working Pressure	
	วงใน Inside Diameter	วงนอก Outside Diameter			psi	bar
3/16"	5.0 + 5.0 mm	12.0 + 12.0 mm	100 m/roll	1 B	250	17
1/4"	6.0 + 6.0 mm	13.0 + 13.0 mm	100 m/roll	1 B	250	17
1/4" x 3/8"	6.0 + 9.0 mm	13.0 + 16.0 mm	100 m/roll	1 B	250	17
5/16"	8.0 + 8.0 mm	15.0 + 15.0 mm	100 m/roll	1 B	250	17